


DJA SERIES


The DJA Series power amplifiers are designed to give you clean, dynamic power with the legendary Studiomaster Professional sound quality & reliability that pros depend on.



- LED indicators on front panel for Power, Signal, Clip, Bass Boost & Protect.




- Rugged & Reliable Professional Stereo Power Amplifier.
- Input: Balanced XLR & 1/4" Jack.
- EQ Processing, Low Cut, Subwoofer selection options on rear panel.
- Stereo, Bridge & Parallel mode selection switch.
- Protection: Temperature, DC Short Circuit.
- Large cooling Fans.
- LED Indicators on front panel for power, Signal, Clip, bass boost & Protect.
- Mains voltage operation 220 - 240 V AC as well as low voltage operation (150V AC).
- Output: Speakon & Binding Post Connectors.
- 19" rack mountable.
- Works on 2 Ohms.



- **BASS BOOST SWITCH (on rear panel)** adds, Low-frequency compensation to enhance speaker output, thus delivering a punchy performance;

Note that this switch is effective only if the FILTER switch is set OFF.



- **FILTER SWITCH (on rear panel)**

- 1) **SUB WOOFER**...by selecting this filter the amplifier outputs the frequencies that are lower than the cut-off set by the FREQUENCY adjustment knob.
- 2) **LOW CUT**...This setting is used to filter out unneeded low or subsonic frequencies.

Technical Specifications

Model	DJA 800	DJA 1600	DJA 2500	DJA 3200	DJA 4000	DJA 5000
Power Output						
4 Ω (True RMS), 20Hz-20kHz, 1% THD	2 x 250 W	2 x 550 W	2 x 900 W	2 x 1125 W	2 x 1400 W	2 x 1900 W
4 Ω (EIA), 1kHz, 1%THD	2 x 415 W	2 x 800 W	2 x 1500 W	2 x 1650 W	2 x 1950 W	2 x 2500 W
8 Ω (True RMS), 20Hz-20kHz, 1% THD	2 x 165 W	2 x 350 W	2 x 600 W	2 x 700 W	2 x 900 W	2 x 1200 W
8 Ω (EIA), 1kHz, 1%THD	2 x 245 W	2 x 560 W	2 x 825 W	2 x 900 W	2 x 1100 W	2 x 1400 W
Bridged Mode						
8 Ω (True RMS), 20Hz-20kHz, 1% THD	525 W	1150 W	1800 W	2250 W	2800 W	3800 W
8 Ω (EIA), 1kHz, 1%THD	830 W	1600 W	3000 W	3300 W	3900 W	5000 W
Damping factor	> 350 :1 (8 Ω)					
Frequency Response	20Hz - 20kHz (-3dB)					
Protection Devices	Temperature, DC, Short Circuit, Soft Start					
Input Connector (Per Channel)	XLR, 1/4" TRS Jack					
Output Connector (Per Channel)	Speakon / Binding Posts / 6.3mm Jack			Speakon / Binding Posts		
Dimensions (W x D x H)mm	482 x 456 x 88 (2U)			482 x 495 x 132 (3U)		482 x 530 x 132 (3U)
Net Weight (Kgs.)	12.5	15	20	25.5	29.5	32

* Design and specification are subject to change without notice.

Stu**diomaster**[®] is a registered trademark of Audioplus in India. © Copyright Audioplus, 2008. All rights reserved. Any unauthorised reproduction or use of logos, images or design elements is strictly prohibited by law. No part of the compilation may be reproduced in any manner or translated without written permission.